

CRAFTY CARBON RR MIND, CARBON/CHERRY RED, 2022

obj. č: 932626637



Odporúčaná cena

10.499 EUR

Technické špecifikácie

vyrábané veľkosti

S: 380mm / M: 420mm / L: 450mm / XL: 490mm

rám

Crafty Stealth Air full Carbon, e-Bike Optimized Zero Suspension System, 150mm travel, Forward Geometry, internal non-removable battery, Boost 12x148mm rear axle, tapered head tube, one-piece Monoblock upper link, HHG internal cable routing, MAX capacity sealed bearings, oversize 17mm axles, integrated dropout speed sensor, exclusive plastic motor covers.

vidlica

Fox 38 29 Float GRIP2 Factory Kashima, 160mm, e-bike optimized, tapered steerer tube, Boost 15x110mm axle, 44mm offset, 68mm OD crown. Settings: high and low-speed compression, high and low-speed rebound, air preload

hlavové zloženie

"Acros custom for 1-1/2"" head tube, angular contact bearings 40x52x7, Internal cable routing"

prehadzovačka

Sram X01 Eagle, Type 3 roller bearing clutch, cage lock, 1x12s, X-Actuation 1:1

radenie

Sram Trigger GX Eagle, 12s, X-Actuation 1:1, single click

brzdové páčky

Sram G2 RSC, SwingLink and lever pivot bearings, tools-free reach and contact point adjust

kluky

Race Face Aeffect ebike, 165mm

riadidlá

Onoff Krypton Carbon 1.0, rise: 25mm, width: 800mm, 9° backsweep, 5° upsweep, 31.8mm barbore

predstavec

Onoff Krypton FG 30mm, CNC, 31.8mm barbore

sedlovka

Fox Transfer Factory Kashima internal, diameter 31.6mm, S size: 363.5x125mm, M/L size: 418.3x150mm, XL size: 475.1x175mm

sedlo

FIZIK Terra Aidon X5 145mm

náboj predný

Mavic, Boost 15x110mm, IS 6 bolts

náboj zadný

Mavic, Boost 12x148mm, ID360 Ratched system, IS 6 bolts, XD freehub

reťaz

Sram NX Eagle, 12s, Powerlock

kazeta

Sram XG-1275, 10-52T, 12s

drôty

Mavic straightpull duble butted, contactless lacing

ráfiky

Mavic E-Deemax S 29, 30mm internal width, Maxtal welded, PFP, tubeless, 28 spokes

plášte

Maxxis Minion DHF 29x2.6, tubeless ready, 3C MAXX TERRA, EXO+ Protection, 120TPI, folding bead,

obj.c.

010.22244

gripy

Onoff Diamond, 1lock-on, 135mm

tlmič

Fox Float-X LV Factory Kashima, 205x65mm. Settings: compression 2 positions lever, low-speed compression, low-speed rebound, air preload. Trunnion top mount, 25x10mm bottom bushings

predná brzda

Sram G2 RSC, 4-piston caliper, Centerline 200mm IS 6 bolts one-piece rotor, steel-backed organic pads

zadná brzda

Sram G2 RSC, 4-piston caliper, Centerline 200mm IS 6 bolts one-piece rotor, steel-backed organic pads

nastavenia tlmiče

medium compression, medium rebound, air volume spacer 0.2

prevodník

Sram X-Sync 2 Eagle 34T, steel, narrow-wide, 104 BCD

pätka k preházovalce

Mondraker M068

motor + batérie

Bosch Performance Line CX Cruise (25Km/h) GEN4 BS3, Bosch Powertube 750Wh, Bosch Kiox 300

Fotogaléria