

# CHASER R, DIRTY WHITE/BLACK, 2023

obj. č: 944872452



## Technické špecifikácie

### vyrábané veľkosti

S: 380mm / M: 420mm / L: 450mm / XL: 490mm

### rám

Chaser 6061 Alloy Stealth Evo, e-Bike Optimized Zero Suspension System, 150mm travel, Forward Geometry, internal non-removable battery, Boost 12x148mm rear axle, tapered head tube, one-piece Monoblock upper link, HHG internal cable routing, MAX capacity sealed bearings, oversize 17mm axles, integrated dropout speed sensor, exclusive plastic motor covers, shock mudguard

### vidlica

Fox 36 29 Float FIT GRIP EVOL Rhythm, 160mm, e-bike tuned, tapered steerer tube, Boost 15x110mm axle, 44mm offset. Settings: sweep adjust compression, Low-speed rebound, air preload

### hlavové zloženie

Onoff Saturn tapered for 1-1/8" to 1-1/2" head tube, ACB sealed bearings, top 41x30.2x7x45°x45°, bottom 51.9x40x8x45°x45°

### prehadzovačka

Sram GX Eagle, Type 3 roller bearing clutch, cage lock, 1x12s, X-Actuation 1:1

### radenie

Sram Trigger SX Eagle, 12s, X-Actuation 1:1, single click

### brzdové páčky

Sram DB8, tool-free reach adjust

### kluky

Race Face Aeffect ebike, 165mm

### riadidlá

Onoff Sulfur 1.0 double butted 6061 alloy, rise: 20mm, width: 800mm, 9° backsweep, 5° upsweep, 31.8mm barbore

### predstavec

Onoff Sulfur FG 30mm 0°, 6061 forged alloy, 31.8mm barbore

### sedlovka

Onoff Pija dropper internal, diameter 31.6mm, S size: 405x95-125mm, M size 458x120-150mm, L size: 498x140-170mm, XL size: 498x140-170mm

### sedlo

MDK ebike black

### náboj predný

Mavic, Boost 15x110mm, IS 6 bolts

### náboj zadný

Mavic, Boost 12x148mm, ID360 Ratched system, IS 6 bolts

### reťaz

Sram SX Eagle, 12s, Powerlock

### kazeta

Sram PG-1210, 11-50T, 12s

### drôty

Mavic J-bend double butted, contactless lacing

### ráfiky

Mavic E-Deemax 29, 30mm internal width, welded, PFP, tubeless ready, 28 spokes

### plášte

Maxxis Rekon 29x2.6, tubeless ready, dual compound, EXO protection, 60TPI, folding bead

### obj.c.

010.23300

### gripy

Onoff Twin, 1lock-on, 135mm

### tlmič

Fox Float DPS Performance, 205x65mm. Settings: Compression 3 positions lever, low-speed rebound, air preload. Trunnion top mount, 25x10mm bottom bushings

**predná brzda**

Sram DB8, 4-piston caliper, Centerline 200mm IS 6 bolts one-piece rotor, steel-backed organic pads

**zadná brzda**

Sram DB8, 4-piston caliper, Centerline 200mm IS 6 bolts one-piece rotor, steel-backed organic pads

**nastavenia tlmiče**

medium compression, medium rebound, air volume spacer 0.4

**prevodník**

Sram X-Sync 2 Eagle 34T, steel, narrow-wide, 104 BCD

**pätka k preházovalce**

Mondraker M068

**motor + batérie**

Bosch Performance Line CX Cruise (25Km/h) Smart System , Bosch Powertube 750Wh, Bosch Intuvia 100 / Bosch Mini Remote / Bosch System Controller

**Fotogaléria**