

SUPERFOXY R, FROST GREEN/BLACK/ÖHLINS YELLOW, 2022

obj. č.: 932626637



Technické špecifikácie

vyrábané veľkosti

S: 380mm / M: 420mm / L: 470mm / XL: 510mm

rám

SuperFoxy 29 6061 Alloy Stealth Evo, hydroformed tubing, Zero Suspension System, 160mm travel, Forward Geometry, one piece Monoblock upper link, SuperBoost 12x157mm rear axle, tapered head tube, 73mm BSA bottom bracket, dedicated 1x drivetrain design, telescopic seatpost internal routing, Max. capacity sealed bearings, ISCG 05

vidlica

Öhlins RXF 38 M.2 29, 170mm, TTX18 Twin Tube cartridge, tapered steerer tube, Boost 15x110mm axle, offset 44mm. Settings: high speed compression lever with climb mode, low-speed compression, rebound, air preload, ramp chamber

hlavové zloženie

Onoff Saturn tapered for 1-1/8" to 1-1/2" head tube, ACB sealed bearings, top 41x30.2x7x45°x45°, bottom 51.9x40x8x45°x45°

prehadzovačka

Sram NX Eagle, Type 3 roller bearing clutch, cage lock, long cage, 1x12s, X-actuation 1:1

radenie

Sram Trigger SX Eagle, 12s, X-Actuation 1:1

brzdové páčky

Sram Code R, tool-free reach adjust

kluky

Truvativ Descendant 7K Eagle, SuperBoost, DUB axle, Direct mount chain ring, S/M size: 170mm, L/XL size: 175mm

stredové zloženie

Sram DUB BSA, sealed bearings, 73mm

riadidlá

Onoff Sulfur 1.0 double butted 6061 alloy, rise: 20mm, width: 800mm, 9° backsweep, 5° upsweep, 31.8mm barbare

predstavec

Onoff Sulfur FG 30mm 0°, 6061 forged alloy, 31.8mm barbare

sedlovka

Onoff Pija dropper internal, diameter 31.6mm, S size: 337x100mm, M size 387x125mm, L size: 425x150mm, XL size: 465x170mm

sedlo

SDG BEL-AIR 3.0, LPU foam, steel rails

náboj predný

Mavic, Boost 15x110mm, IS 6 bolts

náboj zadný

Mavic, SuperBoost 12x157mm, ID360 Ratched system, IS 6 bolts

reťaz

Sram SX Eagle, 12s, Powerlock

kazeta

Sram XG-1230, 11-50T, 12s

drôty

Mavic J-bend duble butted

ráfiky

Mavic Custom Deemax 29, 28mm internal width, Maxtal welded rim, tubeless ready, 28 spokes

plášte

Maxxis Assegai 29x2.5WT, Maxxis Dissector 29x2.4WT, tubeless ready, 3C MAXX GRIP compound, DH casing, 60x2TPI, folding beadtubeless ready, 3C MAXX GRIP compound, DH casing, 60x2TPI, folding bead,

obj.c.

010.22076

gripy

Onoff Diamond, 1lock-on, 135mm

tlmič

Öhlins TTX Air 205X65mm. Settings: high speed compression lever with climb mode, low-speed compression, rebound, air preload. Trunnion top mount, 22.2x10mm bottom bushings

predná brzda

Sram Code R, oversized 4-piston caliper, Centerline 200mm IS 6 bolts one-piece rotor, steel-backed metal sintered pads

zadná brzda

Sram Code R, oversized 4-piston caliper, Centerline 200mm IS 6 bolts one-piece rotor, steel-backed metal sintered pads

nastavenia tlmiče

C20 compression, R35 rebound

prevodník

32T, CNC-machined alloy, X-SYNC 2

pätka k prehadzovačce

Mondraker M068

Fotogaléria