

SUSPENSION SETUP

RAZE RR TRAIL

Fork: Fox 36 29 Float GRIP2 Factory Kashima, 150mm

Follow Fox 36 Float GRIP2 Factory Kashima recommended settings on the bottom right back side of the casting. Mondraker recommended Fox 36 Float GRIP2 Factory Kashima fork settings based on rider weight and Trail application:

| SAG | | RECOMMENDED SETTING | | | |
|-----------------------------|-------------|-----------------------------|-----|-----|-----|
| RIDER WEIGHT | AIR PRESURE | CLICS OUT FROM FULLY CLOSED | | | |
| lbs / kg | psi | HSR | LSR | HSC | LSC |
| <121-128lbs / <55-58 kg | 55 | 9 | 16 | 7 | 16 |
| 129,8-136,4lbs / 59-62 kg | 59 | 8-7 | 15 | 7 | 15 |
| 138,6-145,2lbs / 63-66 kg | 63 | 8-7 | 14 | 7-6 | 14 |
| 147,4-154lbs / 67-70 kg | 67 | 7-6 | 13 | 7-6 | 13 |
| 156,2-162,8lbs / 71-74 kg | 71 | 7-6 | 12 | 6-5 | 12 |
| 165-171,6lbs / 75-78 kg | 75 | 6-5 | 11 | 6-5 | 11 |
| 173,8-180,4lbs / 79-82 kg | 79 | 6-5 | 10 | 5-4 | 10 |
| 182,6-189,2lbs / 83-86 kg | 83 | 5-4 | 9 | 5-4 | 9 |
| 191,4-198lbs / 87-90 kg | 87 | 5-4 | 8 | 4-3 | 8 |
| 200,2-206,8lbs / 91-94 kg | 91 | 4-3 | 7 | 4-3 | 7 |
| 209-215,6lbs / 95-98 kg | 95 | 4-3 | 6 | 3-2 | 6 |
| 217,8-224,4lbs / 99-102 kg | 99 | 3-2 | 5 | 3-2 | 5 |
| 226,6-233,2lbs / 103-106 kg | 103 | 3-2 | 4 | 2-1 | 4 |
| 235,4-242lbs / 107-110 kg | 107 | 2-1 | 3 | 2-1 | 3 |
| 244,2-250,8lbs / 111-114 kg | 111 | 2-1 | 2 | 1 | 2 |
| >253-319lbs / >115-145 kg | 115 | 1 | 1 | 1 | 1 |

*Suggested fork sag 20%

These values offer a general recommendation. Rebound and compression damping settings are a personal choice and should be fine-tuned depending on the riding style and terrain conditions.

Rear shock: Fox Float DPS Factory Kashima EVOL LV

| SAG | | RECOMMENDED SETTING | |
|-----------------------------|-------------|-----------------------------|-------|
| RIDER WEIGHT | AIR PRESURE | CLICS OUT FROM FULLY CLOSED | |
| lbs / kg | psi | LSC | LSR |
| <121-128lbs / <55-58 kg | 100 | open | 11 |
| 129,8-136,4lbs / 59-62 kg | 108 | open | 11-10 |
| 138,6-145,2lbs / 63-66 kg | 116 | open | 11-10 |
| 147,4-154lbs / 67-70 kg | 124 | open | 10-9 |
| 156,2-162,8lbs / 71-74 kg | 132 | open | 10-9 |
| 165-171,6lbs / 75-78 kg | 140 | open | 9-8 |
| 173,8-180,4lbs / 79-82 kg | 148 | open | 9-8 |
| 182,6-189,2lbs / 83-86 kg | 156 | open | 8-7 |
| 191,4-198lbs / 87-90 kg | 164 | open | 8-7 |
| 200,2-206,8lbs / 91-94 kg | 172 | open | 7-6 |
| 209-215,6lbs / 95-98 kg | 180 | open | 7-6 |
| 217,8-224,4lbs / 99-102 kg | 188 | mid | 6-5 |
| 226,6-233,2lbs / 103-106 kg | 196 | mid | 4-3 |
| 235,4-242lbs / 107-110 kg | 204 | mid | 3-2 |
| 244,2-250,8lbs / 111-114 kg | 212 | mid | 2-1 |
| >253-319lbs / >115-145 kg | 220 | mid | 1 |

*Settings based on Downhill application and 30-35% recommended sag