F-PODIUM CARBON R, CARBON/MARLIN BLUE, 2022

obj. č: 932626637



Odporúčaná cena
7.299 EUR
Akčná cena
5.169 EUR

Technické špecifikácie

vyrábané veľkosti
S: 390mm / M: 420mm / L: 470mm / XL: 510mm

rám
F-Podium 29 Stealth Air Full Carbon, XCO Optimized Zero Suspension System, 100mm, XC Forward Geometry, Carbon Monoblock upper link, BSA bottom bracket, tapered head tube, HHG internal cable routing, dedicated 1X drivetrain design, Boost 12x148mm rear axle, shock mudguard, postmount rear brake mount.

vidlica
Fox 34 Step Cast Float FIT4 Evol Factory Kashima, 110mm, tapered steerer tube,15x110mm Boost axle, offset 44mm. Settings: remote 2pos Push-unlock, compression micro-adjustment at low-speed, rebound, air preload

hlavové zloženie
Acros AZX-239 R1 Block Lock, ZS44/28.6 top, ZS56/40 bottom

prehadzovačka
Sram X01 Eagle, Type 3 roller bearing clutch, cage lock, 1x12s, X-Actuation 1:1

radenie
Sram Trigger GX Eagle, 12s, X-Actuation 1:1

brzdové páčky
Sram Level TL, Direct Link actuation, tooled reach adjust, lever pivot bushings

kľuky
Sram X1 Carbon Eagle, Boost, DUB axle, Direct mount chain ring, S size: 170mm, M/L/XL size: 175mm

stredové zloženie
Sram DUB BSA, sealed bearings, 73mm

riadidlá
Onoff Helium Carbon 0.2, rise: 4.8mm, width: 760mm, 9º backsweep, 0º upsweep, 31.8mm barbore

predstavec
MDK, 6061 T6 Alloy, 31.8mm barbore, rise: +/-5º, length: sizes S/M: 50mm, size L: 60mm, size XL: 70mm

sedlovka
Onoff Helium Carbon 0-R, diameter 31.6mm, length 400mm

sedlo
Fizik Antares R7

náboj predný
Mavic, Boost 15x110mm, IS 6 bolts

náboj zadný
Mavic, Boost 12x148mm, ID360 Ratched system, IS 6 bolts, XD freehub

reťaz
Sram GX Eagle, 12s, Powerlock

kazeta
Sram XG-1275, 10-50T, 12s

drôty
Mavic straightpull duble butted, contactless lacing

ráfiky
Mavic Crossmax Carbon XL R 29, 30mm internal width, hookless, tubeless ready, 24 spokes

plášte
Maxxis Rekon Race 29x2.35, EXO protection, tubeless ready, 120TPI, folding bead, Maxxis Rekon Race 29x2.35, EXO protection, tubeless ready, 120TPI, folding bead

obj.c.
010.22048

gripy
Onoff Diamond, 1lock-on, 135mm

tlmič Fox Float DPS SV EVOL Factory Kashima, 185x47,5mm. Settings: 2 position remote compression (open/lock), low-speed rebound, air preload. Trunnion top mount, 22.2x10mm bottom bushings	**predná brzda** Sram Level TL, 2 piece caliper, Centerline 180mm IS 6 bolts one-piece rotor, steel-backed organic pad
zadná brzda Sram Level TL, 2 piece caliper, Centerline 160mm IS 6 bolts one-piece rotor, steel-backed organic pad	**nastavenia tlmiče** Firm compression, light rebound, air volume spacer 0.2
prevodník 34T, CNC-machined alloy, X-SYNC 2	**pätka k přehazovačce** Sram UDH

Fotogaléria



