

F-PODIUM CARBON R, CARBON/BRITISH RACING GREEN/RACING SILVER, 2023

obj. č.: 944872452

Odporúčaná cena
7.499 EUR



Technické špecifikácie

vyrábané veľkosti

S: 380mm / M: 420mm / L: 470mm / XL: 510mm

vidlica

Fox 34 Step Cast Float FIT4 EVOL Factory Kashima, 110mm, tapered steerer tube, 15x110mm Boost axle, offset 44mm. Settings: remote 2pos Push-unlock, compression micro-adjustment at low-speed, rebound, air preload, Fox dual pull

prehadzovačka

Sram X01 Eagle, Type 3 roller bearing clutch, cage lock, 1x12s, X-Actuation 1:1

brzdové páčky

Sram Level TL, Direct Link actuation, tooled reach adjust, lever pivot bushings

stredové zloženie

Sram DUB BSA, sealed bearings, 73mm

predstavec

MDK, 6061 T6 Alloy, 31.8mm barbore, rise: +/-5°, length: sizes S/M: 50mm, size L: 60mm, size XL: 70mm

sedlo

Fizik Antares R7

náboj zadný

Mavic, Boost 12x148mm, ID360 Ratchet system, IS 6 bolts, XD freehub

kazeta

Sram XG-1275, 10-50T, 12s

ráfiky

Mavic Crossmax Carbon XL R 29, 30mm internal width, hookless, tubeless ready, 24 spokes

obj.c.

010.23057

rám

F-Podium 29 Stealth Air Full Carbon, XCO Optimized Zero Suspension System, 100mm, XC Forward Geometry, Carbon Monoblock upper link, BSA bottom bracket, tapered head tube, HHG internal cable routing, dedicated 1X drivetrain design, Boost 12x148mm rear axle, shock mudguard, postmount rear brake mount.

hlavové zloženie

Acros AZX-239 R1 Block Lock, ZS44/28.6 top, ZS56/40 bottom

radenie

Sram Trigger GX Eagle, 12s, X-Actuation 1:1

kluky

Sram X1 Carbon Eagle, Boost, DUB axle, Direct mount chain ring, S size: 170mm, M/L/XL size: 175mm

riadidlá

Onoff Helium Carbon 0.2, rise: 4.8mm, width: 760mm, 9° backsweep, 0° upsweep, 31.8mm barbore

sedlovka

Onoff Helium Carbon 0-R, diameter 31.6mm, length 400mm

náboj predný

Mavic, Boost 15x110mm, IS 6 bolts

reťaz

Sram GX Eagle, 12s, Powerlock

drôty

Mavic straight-pull double butted, contactless lacing

plášte

Maxxis Rekon Race 29x2.35, EXO protection, tubeless ready, 120TPI, folding bead

gripy

Onoff Desert, 1lock-on, 135mm

tlmič Fox Float DPS SV EVOL Factory Kashima, 185x47,5mm. Settings: 2 position remote compression (open/lock), low-speed rebound, air preload. Trunnion top mount, 22.2x10mm bottom bushings	predná brzda Sram Level TL, 2 piece caliper, Centerline 180mm IS 6 bolts one-piece rotor, steel-backed organic pad
zadná brzda Sram Level TL, 2 piece caliper, Centerline 180mm IS 6 bolts one-piece rotor, steel-backed organic pad	nastavenia tlmiče Firm compression, light rebound, air volume spacer 0.2
prevodník 34T, CNC-machined alloy, X-SYNC 2	pätka k pŕehazovačce Sram UDH

Fotogaléria

