

CHASER 750, CHERRY RED/BLACK, 2022

obj. č: 932626637



Odporúčaná cena

5.999 EUR

Technické špecifikácie

vyrábané veľkosti

S: 380mm / M: 420mm / L: 450mm / XL: 490mm

hmotnosť

24,8 Kg

rám

Chaser 6061 Alloy Stealth Evo, e-Bike Optimized Zero Suspension System, 150mm travel, Forward Geometry, internal non-removable battery, Boost 12x148mm rear axle, tapered head tube, one-piece Monoblock upper link, HHG internal cable routing, MAX capacity sealed bearings, oversize 17mm axles, integrated dropout speed sensor, exclusive plastic motor covers, shock mudguard

vidlica

Fox 36 29 Float FIT GRIP EVOL Rythm, 160mm, e-bike tuned, tapered steerer tube, Boost 15x110mm axle, 44mm offset. Settings: sweep adjust compression, Low-speed rebound, air preload

hlavové zloženie

Onoff Saturn tapered for 1-1/8" to 1-1/2" head tube, ACB sealed bearings, top 41x30.2x7x45°x45°, bottom 51.9x40x8x45°x45°

prehadzovačka

Sram SX Eagle, Type 3 roller bearing clutch, cage lock, long cage, 1x12s, X-actuation 1:1

radenie

Sram Trigger SX Eagle, 12s, X-Actuation 1:1, single click

brzdové páčky

Sram G2 R, tool-free reach adjust

kľuky

Race Face Aeffect ebike, 165mm

riadičlá

Onoff Sulfur 1.0 double butted 6061 alloy, rise: 20mm, width: 800mm, 9° backsweep, 5° upsweep, 31.8mm barbore

predstavec

Onoff Sulfur FG 30mm 0°, 6061 forged alloy, 31.8mm barbore

sedlovka

Onoff Pija dropper internal, diameter 31.6mm, S size: 387x125mm, M size: 425x150mm, L/XL size: 465x170mm

sedlo

FIZIK Terra Aidon X5 145mm

náboj predný

Formula DC711, Boost 15x110mm, sealed bearings, IS 6 bolts

náboj zadný

Formula EHL148 Boost 12x148mm, sealed bearings, IS 6 bolts

reťaz

Sram SX Eagle, 12s, Powerlock

kazeta

Sram PG-1210, 11-50T, 12s

drôty

CN round stainless steel

ráfiky

MDK-HP1 29, 30mm internal width, tubeless ready, 32 spokes

plášte

Maxxis Rekon 29x2.6, tubeless ready, dual compound, EXO protection, 60TPI, folding bead, Maxxis Rekon 29x2.6, tubeless ready, dual compound, EXO protection, 60TPI, folding bead

obj.c.

010.22300

gripy

Onoff Diamond, 1lock-on, 135mm

tlmič

RockShox Deluxe Select R Debonair, 205x65mm. Settings: Low-speed rebound, air preload. Trunnion top mount, 25x10mm bottom bushings

predná brzda

Sram G2 R, 4-piston caliper, Centerline 200mm IS 6 bolts one-piece rotor, steel-backed organic pads

zadná brzda

Sram G2 R, 4-piston caliper, Centerline 200mm IS 6 bolts one-piece rotor, steel-backed organic pads

prevodník

Sram X-Sync 2 Eagle 34T, steel, narrow-wide, 104 BCD

pätka k přehazovačce

Mondraker M068

motor + batérie

Bosch Performance Line CX Cruise (25Km/h) GEN4 BS3, Bosch Performance Line CX Cruise (25Km/h) GEN4 BS3 , Bosch Powertube 750Wh,Bosch Kiox 300