

F-PODIUM CARBON, CARBON/DIRTY WHITE, 2022

obj. č.: 932626637



Technické špecifikácie

vyrábané veľkosti S: 390mm / M: 420mm / L: 470mm / XL: 510mm	hmotnosť 11,5 Kg
rám F-Podium 29 Stealth Air Full Carbon, XCO Optimized Zero Suspension System, 100mm, XC Forward Geometry, Carbon Monoblock upper link, BSA bottom bracket, tapered head tube, HHG internal cable routing, dedicated 1X drivetrain design, Boost 12x148mm rear axle, shock mudguard, postmount rear brake mount.	vidlica Fox 34 Step Cast Float Grip Evol Performance, 110mm, tapered steerer tube, 15x110mm Boost axle, offset 44mm. Settings: remote 2pos Push-unlock, rebound, air preload
hlavové zloženie Acros AZX-239 R1 Block Lock, ZS44/28.6 top, ZS56/40 bottom	prehadzovačka Sram GX Eagle, Type 3 roller bearing clutch, cage lock, 1x12s, X-Actuation 1:1
radenie Sram Trigger SX Eagle, 12s, X-Actuation 1:1	brzdové páčky Sram Level T, Direct Link actuation, tooled reach adjust, lever pivot bushings
kľuky Truvativ Stylo 6K Eagle, 12s, Boost, DUB axle, Direct Mount chain ring, S size: 170mm, M/L/XL size: 175mm	stredové zloženie Sram DUB BSA, sealed bearings, 73mm
riadidlá Onoff Sulfur 0.2, double butted 6061 alloy, rise: 4.8mm, width: 760mm, 9° backsweep, 0° upsweep, 31.8mm barbore	predstavec MDK, 6061 T6 Alloy, 31.8mm barbore, rise: +/-5°, length: sizes S/M: 50mm, size L: 60mm, size XL: 70mm
sedlovka Onoff Sulfur 0-R, 6061 T6 Alloy, 3D forged, diameter 31.6mm, length 400mm	sedlo Fizik Antares R7
náboj predný Mavic, Boost 15x110mm, IS 6 bolts	náboj zadný Mavic, Boost 12x148mm, ID360 Ratched system, IS 6 bolts
reťaz Sram SX Eagle, 12s, Powerlock	kazeta Sram PG-1230, 11-50T, 12s
drôty Mavic straightpull double butted, contactless lacing	ráfiky Mavic Crossmax 29, 25mm internal width, welded rim, hookless, tubeless ready, 24 spokes
plášte Maxxis Rekon Race 29x2.35, EXO protection, tubeless ready, 120TPI, folding bead, Maxxis Rekon Race 29x2.35, EXO protection, tubeless ready, 120TPI, folding bead	obj.c. 010.22044

gripy

Onoff Diamond, 1lock-on, 135mm

tlmič

Fox Float DPS SV Performance Elite, 185x47,5mm. Settings: 2 position remote compression (open/lock), low-speed rebound, air preload. Trunnion top mount, 22.2x10mm bottom bushings

predná brzda

Sram Level T, 2 piece caliper, Centerline 180mm IS 6 bolts one-piece rotor, steel-backed organic pad

zadná brzda

Sram Level T, 2 piece caliper, Centerline 160mm IS 6 bolts one-piece rotor, steel-backed organic pad

nastavenia tlmiče

Firm compression, light rebound, air volume spacer 0.2

prevodník

34T, steel, X-Sync 2

pätka k preházoľače

Sram UDH

Fotogaléria