

CHASER R, MARLIN BLUE/BLACK, 2022

obj. č: 932626637



Technické špecifikácie

vyrábané veľkosti S: 380mm / M: 420mm / L: 450mm / XL: 490mm	hmotnosť 24,6kg
rám Chaser 6061 Alloy Stealth Evo, e-Bike Optimized Zero Suspension System, 150mm travel, Forward Geometry, internal non-removable battery, Boost 12x148mm rear axle, tapered head tube, one-piece Monoblock upper link, HHG internal cable routing, MAX capacity sealed bearings, oversize 17mm axles, integrated dropout speed sensor, exclusive plastic motor covers, shock mudguard	vidlica Fox 36 29 Float FIT GRIP EVOL Rythm, 160mm, e-bike tuned, tapered steerer tube, Boost 15x110mm axle, 44mm offset. Settings: sweep adjust compression, Low-speed rebound, air preload
hlavové zloženie Onoff Saturn tapered for 1-1/8" to 1-1/2" head tube, ACB sealed bearings, top 41x30.2x7x45°x45°, bottom 51.9x40x8x45°x45°	prehadzovačka Sram GX Eagle, Type 3 roller bearing clutch, cage lock, 1x12s, X-Actuation 1:1
radenie Sram Trigger SX Eagle, 12s, X-Actuation 1:1, single click	brzdové páčky Sram G2 R, tool-free reach adjust
kluky Race Face Aeffect ebike, 165mm	riadidlá Onoff Sulfur 1.0 double butted 6061 alloy, rise: 20mm, width: 800mm, 9° backsweep, 5° upsweep, 31.8mm barbore
predstavec Onoff Sulfur FG 30mm 0°, 6061 forged alloy, 31.8mm barbore	sedlovka Onoff Pija dropper internal, diameter 31.6mm, S size: 387x125mm, M size: 425x150mm, L/XL size: 465x170mm
sedlo FIZIK Terra Aidon X5 145mm	náboj predný Mavic, Boost 15x110mm, IS 6 bolts
náboj zadný Mavic, Boost 12x148mm, ID360 Ratched system, IS 6 bolts	reťaz Sram SX Eagle, 12s, Powerlock
kazeta Sram PG-1210, 11-50T, 12s	drôty Mavic J-bend duble butted, contactless lacing
ráfiky Mavic E-Deemax 29, 30mm internal width, welded, PFP, tubeless ready, 28 spokes	plášte Maxxis Rekon 29x2.6, tubeless ready, dual compound, EXO protection, 60TPI, folding bead, Maxxis Rekon 29x2.6, tubeless ready, dual compound, EXO protection, 60TPI, folding bead
obj.c. 010.22170	gripy Onoff Diamond, 1lock-on, 135mm

tlmič

Fox Float DPS Performance, 205x65mm. Settings: Compression 3 positions lever, low-speed rebound, air preload. Trunnion top mount, 25x10mm bottom bushings

zadná brzda

Sram G2 R, 4-piston caliper, Centerline 200mm IS 6 bolts one-piece rotor, steel-backed organic pads

prevodník

Sram X-Sync 2 Eagle 34T, steel, narrow-wide, 104 BCD

motor + batérie

Bosch Performance Line CX Cruise (25Km/h) GEN4 BS3 , Bosch Powertube 750Wh, Bosch Kiox 300

predná brzda

Sram G2 R, 4-piston caliper, Centerline 200mm IS 6 bolts one-piece rotor, steel-backed organic pads

nastavenia tlmiče

Light compression, Light rebound, 1 Token

pätka k přehazovačce

Mondraker M068

Fotogaléria