

PRIME 29 (SPE), BLACK/RACING SILVER, 2022

obj. č: 932626637



Technické špecifikácie

vyrábané veľkosti XS: 380mm / S: 390mm / M: 430mm / L: 470mm / XL: 510mm	hmotnosť 22,2 Kg
rám Prime Xtralite 6061 Full Butted Alloy, Forward Geometry, internal removable battery with integrated alloy cover, tapered head tube, Boost 12x148mm rear axle, integrated dropout speed sensor	vidlica RockShox Recon Silver RL 29, 120mm, Motion control, Solo Air, tapered steerer tube, Boost 15x110mm axle, 42mm offset. Settings: compression adjustment at low-speed to lock, rebound, air preload
hlavové zloženie Onoff Saturn tapered for 1-1/8" to 1-1/2" head tube, ACB sealed bearings, top 41x30.2x7x45°x45°, bottom 51.9x40x8x45°x45°	prehadzovačka Sram SX Eagle, Type 3 roller bearing clutch, cage lock, long cage, 1x12s, X-actuation 1:1
radenie Sram Trigger SX Eagle, 12s, X-Actuation 1:1, single click	brzdové páčky Sram Level TL, Direct Link actuation, tool-free reach adjust, lever pivot bushings
kluky Race Face Aeffect ebike, 165mm	riadičlá Onoff Sulfur 1.0 double butted 6061 alloy, rise: 20mm, width: 800mm, 9° backsweep, 5° upsweep, 31.8mm bar bore
predstavec Onoff Sulfur FG 30mm 0°, 6061 forged alloy, 31.8mm bar bore	sedlovka Onoff Sulfur 0-R, 6061 T6 Alloy, 3D forged, diameter 31.6mm, length 400mm
sedlo FIZIK Terra Aidon X5 145mm	náboj predný Formula DC711, Boost 15x110mm, sealed bearings, IS 6 bolts
náboj zadný Formula EHL148 Boost 12x148mm, sealed bearings, IS 6 bolts	reťaz Sram SX Eagle, 12s, Powerlock
kazeta Sram PG-1210, 11-50T, 12s	drôty CN round stainless steel
ráfiky MDK-HP1 29, 30mm internal width, tubeless ready, 32 spokes	plášte Maxxis Rekon 29x2.6, tubeless ready, dual compound, EXO protection, 60TPI, folding bead, Maxxis Rekon 29x2.6, tubeless ready, dual compound, EXO protection, 60TPI, folding bead
obj.c. 010.22174SPE	gripy Onoff Diamond, 1 lock-on, 135mm
predná brzda Sram Level TL, 2 piece caliper, Centerline 200mm IS 6 bolts one-piece rotor, steel-backed organic pad	zadná brzda Sram Level TL, 2 piece caliper, Centerline 180mm IS 6 bolts one-piece rotor, steel-backed organic pad
prevodník Sram X-Sync 2 Eagle 34T, steel, narrow-wide, 104 BCD	pätka k prehadzovačke Mondraker M068

motor + batterie

Bosch Performance Line CX Cruise (25Km/h) GEN4, Bosch
Powertube 625Wh, Bosch Purion

Fotogaléria

