

RAZE CARBON R MIND, CARBON/GLOSS BLACK/RACING SILVER, 2022

obj. č.: 932626637



Odporúčaná cena

6.399 EUR

Technické špecifikácie

vyrábané veľkosti S: 380mm / M: 420mm / L: 450mm / XL: 500mm	hmotnosť 13,2 Kg
rám New Trail 29 Stealth Air full Carbon, Zero Suspension System, 130mm travel, Forward Geometry, Carbon Monoblock upper link, Boost 12x148mm rear axle, tapered head tube, 73mm BSA bottom bracket, dedicated 1x drivetrain design, HHG internal cable routing, Enduro MAX sealed bearings, shock mudguard, ISCG 05, custom frame protectors.	vidlica Fox 36 29 Float GRIP EVOL Performance, 150mm, tapered steerer tube, Boost 15x110mm axle, 44mm offset. Settings: 3 positions with micro adjust compression, low-speed rebound, air preload
hlavové zloženie Acros custom for 1-1/2	prehadzovačka Sram GX Eagle, Type 3 roller bearing clutch, cage lock, 1x12s, X-Actuation 1:1
radenie Sram Trigger NX Eagle, 12s, X-Actuation 1:1	brzdové páčky Sram G2, SwingLink, tool-free reach adjust
kluky Truvativ Stylo 7k Eagle, Boost, DUB axle, Direct mount chain ring, S/M size: 170mm, L/XL size: 175mm	stredové zloženie Sram DUB BSA, sealed bearings, 73mm
riadidlá Onoff Sulfur 1.0 double butted 6061 alloy, rise: 20mm, width: 800mm, 9° backsweep, 5° upsweep, 31.8mm barbare	predstavec Onoff Sulfur FG 30mm 0°, 6061 forged alloy, 31.8mm barbare
sedlovka Onoff Pija dropper internal, diameter 31.6mm, S size: 387x125mm, M size: 425x150mm, L/XL size: 465x170mm	sedlo Fizik Antares R7
náboj predný DT 350, Boost 15x110mm, IS 6 bolts	náboj zadný DT 350, Boost 12x148mm, 36T SL Ratchet system, IS 6 bolts, XD freehub
reťaz Sram NX Eagle, 12s, Powerlock	kazeta Sram XG-1275, 10-52T, 12s
drôty DT Competition, straightpull	ráfiky DT Swiss XM1700 Spline 29, 30mm internal width, welded aluminum, tubeless ready, 28 spokes
plášte Maxxis Aggressor 29x2.3, tubeless ready, dual compound, Exo protection, 60TPI, folding bead, Maxxis Dissector 29x2.4 WT, tubeless ready, 3C MAXX TERRA compound, EXO+ protection, 120TPI, folding bead	obj.c. 010.22304

gripy

Onoff Diamond, 1lock-on, 135mm

tlmič

Fox Float DPS LV EVOL Performance, 205x57.5mm.
Settings: rebound, 3-position compression adjustment (Open/Mid/Lock), air preload. Trunnion top mount, 30x8mm bottom bushings

predná brzda

Sram G2, 4-piston caliper, Centerline 180mm IS 6 bolts one-piece rotor, steel-backed organic pads

zadná brzda

Sram G2, 4-piston caliper, Centerline 180mm IS 6 bolts one-piece rotor, steel-backed organic pads

nastavenia tlmiče

Light compression, extralight rebound, air volume spacer 0.6

prevodník

32T, CNC-machined alloy, X-SYNC 2

pätka k přehazovačce

Sram UDH

Fotogaléria