

CRAFTY R, BLACK/GRAPHITE, 2022

obj. č.: 932626637



Technické špecifikácie

vyrábané veľkosti

S: 380mm / M: 420mm / L: 450mm / XL: 490mm

hmotnosť

25,1kg

rám

Crafty 6061 Alloy Stealth Evo, e-Bike Optimized Zero Suspension System, 150mm travel, Forward Geometry, internal non-removable battery, Boost 12x148mm rear axle, tapered head tube, one-piece Monoblock upper link, HHG internal cable routing, MAX capacity sealed bearings, oversize 17mm axles, integrated dropout speed sensor, exclusive plastic motor covers.

vidlica

Fox 38 29 Float FIT GRIP EVOL Performance, 160mm, e-bike tuned, tapered steerer tube, Boost 15x110mm axle, 44mm offset. Settings: 3 positions with micro adjust compression, low-speed rebound, air preload

hlavové zloženie

Onoff Saturn tapered for 1-1/8" to 1-1/2" head tube, ACB sealed bearings, top 41x30.2x7x45°x45°, bottom 51.9x40x8x45°x45°

prehadzovačka

Sram GX Eagle, Type 3 roller bearing clutch, cage lock, 1x12s, X-Actuation 1:1

radenie

Sram Trigger NX Eagle, 12s, X-Actuation 1:1, single click

brzdové páčky

Sram G2 R, tool-free reach adjust

kluky

Race Face Aeffect ebike, 165mm

riadidlá

Onoff Sulfur 1.0 double butted 6061 alloy, rise: 20mm, width: 800mm, 9° backsweep, 5° upsweep, 31.8mm barbare

predstavec

Onoff Sulfur FG 30mm 0°, 6061 forged alloy, 31.8mm barbare

sedlovka

Onoff Pija dropper internal, diameter 31.6mm, S size: 387x125mm, M size: 425x150mm, L/XL size: 465x170mm

sedlo

FIZIK Terra Aidon X5 145mm

náboj predný

Mavic, Boost 15x110mm, IS 6 bolts

náboj zadný

Mavic, Boost 12x148mm, ID360 Ratched system, IS 6 bolts

reťaz

Sram SX Eagle, 12s, Powerlock

kazeta

Sram PG-1210, 11-50T, 12s

drôty

Mavic J-bend duble butted, contactless lacing

ráfiky

Mavic E-Deemax 29, 30mm internal width, welded, PFP, tubeless ready, 28 spokes

plášte

Maxxis Minion DHF 29x2.6, tubeless ready, 3C MAXX TERRA, EXO+ Protection, 120TPI, folding bead, Maxxis Minion DHR II 29x2.6, tubeless ready, 3C MAXX TERRA, EXO+ Protection, 120TPI, folding bead

obj.c.

010.22224

gripy

Onoff Diamond, 1lock-on, 135mm

tlmič

Fox Float-X LV Performance, 205x65mm. Settings: compression 2 positions lever, low-speed rebound, air preload. Trunnion top mount, 25x10mm bottom bushings

predná brzda

Sram G2 R, 4-piston caliper, Centerline 200mm IS 6 bolts one-piece rotor, steel-backed organic pads

zadná brzda

Sram G2 R, 4-piston caliper, Centerline 200mm IS 6 bolts one-piece rotor, steel-backed organic pads

nastavenia tlmiče

medium compression, medium rebound, air volume spacer 0.2

prevodník

Sram X-Sync 2 Eagle 34T, steel, narrow-wide, 104 BCD

pätka k přehazovačce

Mondraker M068

motor + batérie

Bosch Performance Line CX Cruise (25Km/h) GEN4 BS3, Bosch Powertube 750Wh, Bosch Kiox 300

Fotogaléria