

SUPERFOXY CARBON RR, CARBON/BRITISH RACING GREEN/ÖHLINS YELLOW, 2022

obj. č.: 932626637



Odporúčaná cena
8.599 EUR

Technické špecifikácie

vyrábané veľkosti

S: 380mm / M: 420mm / L: 470mm / XL: 510mm

rám

SuperFoxy 29 Stealth Air full Carbon, Zero Suspension System, 160mm travel, Forward Geometry, Carbon Monoblock upper link, SuperBoost 12x157mm rear axle, tapered head tube, 73mm BSA bottom bracket, dedicated 1x drivetrain design, HHG internal cable routing, Enduro MAX sealed bearings, shock mudguard, ISCG 05, custom frame protectors. *Geometry kit included

vidlica

Öhlins RXF 38 M.2 29, 170mm, TTX18 Twin Tube cartridge, tapered steerer tube, Boost 15x110mm axle, offset 44mm. Settings: high speed compression lever with climb mode, low-speed compression, rebound, air preload, ramp chamber

hlavové zloženie

Onoff Titan tapered for 1-1/8" to 1-1/2" head tube, ACB sealed bearings, top 41.8x30.5x8x45°x45°, bottom 51.9x40x8x45°x45°

prehadzovačka

Sram X01 Eagle, Type 3 roller bearing clutch, cage lock, 1x12s, X-Actuation 1:1

radenie

Sram Trigger X01 Eagle, 12s, X-Actuation 1:1

brzdové páčky

Sram Code RSC, SwingLink and lever pivot bearings, tools-free reach and contact point adjust

kľuky

Sram X01 Carbon Eagle, SuperBoost, DUB axle, Direct mount chain ring, S/M size: 170mm, L/XL size: 175mm

stredové zloženie

Sram DUB BSA, sealed bearings, 73mm

riadidlá

Onoff Krypton Carbon 1.0, rise: 25mm, width: 800mm, 9° backsweep, 5° upsweep, 31.8mm barbore

predstavec

Onoff Krypton FG 30mm, CNC, 31.8mm barbore

sedlovka

Fox Transfer Factory Kashima internal, diameter 31.6mm, S size: 363.5x125mm, M/L size: 418.3x150mm, XL size: 475.1x175mm

sedlo

SDG BEL-AIR 3.0, LPU foam, steel rails

náboj predný

e*thirteen Boost 15x110mm, triple-sealed, fully machined aluminum, IS 6 bolts

náboj zadný

e*thirteen Superboost 12x157mm, triple-sealed, fully machined aluminum w/6-degree engagement, IS 6 bolts, XD freehub

reťaz

Sram GX Eagle, 12s, Powerlock

kazeta

Sram XG-1275, 10-52T, 12s

drôty

e*thirteen custom Hive triple-buttressed black alloy, alloy nipples, nipple washers

ráfiky

e*thirteen LG1 Plus Enduro, IW30 Hookless, 6069 Welded Aluminum, 30mm internal width, tubeless ready, 28 spokes

plášte

Maxxis Assegai 29x2.5WT, tubeless ready, 3C MAXX GRIP compound, DH casing, 60x2TPI, folding bead, Maxxis Dissector 29x2.4WT, tubeless ready, 3C MAXX GRIP compound, DH casing, 60x2TPI, folding bead

obj.c.
010.22118

gripy
Onoff Diamond, 1lock-on, 135mm

tlmič
Ůhlins TTX 22M Coil 205X65mm. Settings: high speed compression lever with climb mode, low-speed compression, rebound, air preload. Trunnion top mount, 22.2x10mm bottom bushings

predná brzda
Sram Code RSC, oversized 4-piston caliper, Centerline 200mm IS 6 bolts one-piece rotor, steel-backed metal sintered pads

zadná brzda
Sram Code RSC, oversized 4-piston caliper, Centerline 200mm IS 6 bolts one-piece rotor, steel-backed metal sintered pads

nastavenia tlmiče
C20 compression, R35 rebound

prevodník
32T, CNC-machined alloy, X-SYNC 2

pätka k přehazovačce
Mondraker M071

ostatné
*Geometry kit included: 0° headset cups and chainstay adaptor for 450mm CS length

Fotogaléria

