

SUPERFOXY CARBON RR, CARBON/BRITISH RACING GREEN/ÖHLINS YELLOW, 2022

obj. č.: 932626637



Technické špecifikácie

vyrábané veľkosti S: 380mm / M: 420mm / L: 470mm / XL: 510mm	rám SuperFoxy 29 Stealth Air full Carbon, Zero Suspension System, 160mm travel, Forward Geometry, Carbon Monoblock upper link, SuperBoost 12x157mm rear axle, tapered head tube, 73mm BSA bottom bracket, dedicated 1x drivetrain design, HHG internal cable routing, Enduro MAX sealed bearings, shock mudguard, ISCG 05, custom frame protectors. *Geometry kit included
vidlica Öhlins RXF 38 M.2 29, 170mm, TTX18 Twin Tube cartridge, tapered steerer tube, Boost 15x110mm axle, offset 44mm. Settings: high speed compression lever with climb mode, low-speed compression, rebound, air preload, ramp chamber	hlavové zloženie Onoff Titan tapered for 1-1/8" to 1-1/2" head tube, ACB sealed bearings, top 41.8x30.5x8x45°x45°, bottom 51.9x40x8x45°x45°
prehadzovačka Sram X01 Eagle, Type 3 roller bearing clutch, cage lock, 1x12s, X-Actuation 1:1	radenie Sram Trigger X01 Eagle, 12s, X-Actuation 1:1
brzdové páčky Sram Code RSC, SwingLink and lever pivot bearings, tools-free reach and contact point adjust	kluky Sram X01 Carbon Eagle, SuperBoost, DUB axle, Direct mount chain ring, S/M size: 170mm, L/XL size: 175mm
stredové zloženie Sram DUB BSA, sealed bearings, 73mm	riadidlá Onoff Krypton Carbon 1.0, rise: 25mm, width: 800mm, 9° backsweep, 5° upsweep, 31.8mm barbare
predstavec Onoff Krypton FG 30mm, CNC, 31.8mm barbare	sedlovka Fox Transfer Factory Kashima internal, diameter 31.6mm, S size: 363.5x125mm, M/L size: 418.3x150mm, XL size: 475.1x175mm
sedlo SDG BEL-AIR 3.0, LPU foam, steel rails	náboj predný e*thirteen Boost 15x110mm, triple-sealed, fully machined aluminum, IS 6 bolts
náboj zadný e*thirteen Superboost 12x157mm, triple-sealed, fully machined aluminum w/6-degree engagement, IS 6 bolts, XD freehub	reťaz Sram GX Eagle, 12s, Powerlock
kazeta Sram XG-1275, 10-52T, 12s	drôty e*thirteen custom Hive triple-buttet black alloy, alloy nipples, nipple washers

ráfiky

e*thirteen LG1 Plus Enduro, IW30 Hookless, 6069 Welded Aluminum, 30mm internal width, tubeless ready, 28 spokes

plášte

Maxxis Assegai 29x2.5WT, tubeless ready, 3C MAXX GRIP compound, DH casing, 60x2TPI, folding bead, Maxxis Dissector 29x2.4WT, tubeless ready, 3C MAXX GRIP compound, DH casing, 60x2TPI, folding bead

obj.c.

010.22118

gripy

Onoff Diamond, 1lock-on, 135mm

tlmič

Öhlins TTX 22M Coil 205X65mm. Settings: high speed compression lever with climb mode, low-speed compression, rebound, air preload. Trunnion top mount, 22.2x10mm bottom bushings

predná brzda

Sram Code RSC, oversized 4-piston caliper, Centerline 200mm IS 6 bolts one-piece rotor, steel-backed metal sintered pads

zadná brzda

Sram Code RSC, oversized 4-piston caliper, Centerline 200mm IS 6 bolts one-piece rotor, steel-backed metal sintered pads

nastavenia tlmiče

C20 compression, R35 rebound

prevodník

32T, CNC-machined alloy, X-SYNC 2

pätka k přehazovačce

Mondraker M071

ostatné

*Geometry kit included: 0° headset cups and chainstay adaptor for 450mm CS length

Fotogaléria