CRAFTY RR (SPE), MARLIN BLUE/RACING SILVER, 2022

obj. č: 932626637



Odporúčaná cena
7.799 EUR
Akčná cena
5.629 EUR

Technické špecifikácie

vyrábané veľkosti
S: 380mm / M: 420mm / L: 450mm / XL: 490mm

hmotnosť
24,9 Kg

rám
Crafty 6061 Alloy Stealth Evo, e-Bike Optimized Zero Suspension System, 150mm travel, Forward Geometry, internal non-removable battery, Boost 12x148mm rear axle, tapered head tube, one-piece Monoblock upper link, HHG internal cable routing, MAX capacity sealed bearings, oversize 17mm axles, integrated dropout speed sensor, exclusive plastic motor covers.

vidlica
Fox 38 29 Float GRIP2 Factory Kashima, 160mm, e-bike tuned, tapered steerer tube, Boost 15x110mm axle, offset 44mm. Settings: high and low-speed compression, high and low-speed rebound, air preload

hlavové zloženie
Onoff Saturn tapered for 1-1/8” to 1-1/2” head tube, ACB sealed bearings, top 41x30.2x7x45ºx45º, bottom 51.9x40x8x45ºx45º

prehadzovačka
Sram GX Eagle, Type 3 roller bearing clutch, cage lock, 1x12s, X-Actuation 1:1

radenie
Sram Trigger GX Eagle, 12s, X-Actuation 1:1, single click

brzdové páčky
Sram G2 RS, SwingLink and lever pivot bearings, tools-free reach and contact point adjust

kľuky
Race Face Aeffect ebike, 165mm

riadidlá
Onoff Sulfur 1.0 double butted 6061 alloy, rise: 20mm, width: 800mm, 9º backsweep, 5º upsweep, 31.8mm barbore

predstavec
Onoff Sulfur FG 30mm 0º, 6061 forged alloy, 31.8mm barbore

sedlovka
Fox Transfer Factory Kashima internal, diameter 31.6mm, S size: 363.5x125mm, M/L size: 418.3x150mm, XL size: 475.1x175mm

sedlo
FIZIK Terra Aidon X5 145mm

náboj predný
Mavic, Boost 15x110mm, IS 6 bolts

náboj zadný
Mavic, Boost 12x148mm, ID360 Ratched system, IS 6 bolts

reťaz
Sram NX Eagle, 12s, Powerlock

kazeta
Sram XG-1230, 11-50T, 12s

drôty
Mavic J-bend duble butted, contactless lacing

ráfiky
Mavic E-Deemax 29, 30mm internal width, welded, PFP, tubeless ready, 28 spokes

plášte
Maxxis Minion DHF 29x2.6, tubeless ready, 3C MAXX TERRA, EXO+ Protection, 120TPI, folding bead, Maxxis Minion DHR II 29x2.6, tubeless ready, 3C MAXX TERRA, EXO+ Protection, 120TPI, folding bead

obj.c.
010.22232SPE

gripy
Onoff Diamond, 1lock-on, 135mm

tlmič
Fox Float-X LV Factory Kashima, 205x65mm. Settings: compression 2 positions lever, low-speed compression, low-speed rebound, air preload. Trunnion top mount, 25x10mm bottom bushings

predná brzda
Sram G2 RS, 4-piston caliper, Centerline 200mm IS 6 bolts one-piece rotor, steel-backed organic pads

zadná brzda
Sram G2 RS, 4-piston caliper, Centerline 200mm IS 6 bolts one-piece rotor, steel-backed organic pads

nastavenia tlmiče
medium compression, medium rebound, air volume spacer 0.2

prevodník
Sram X-Sync 2 Eagle 34T, steel, narrow-wide, 104 BCD

pätka k přehazovačce
Mondraker M068

motor + batérie
Bosch Performance Line CX Cruise (25Km/h) GEN4 BS3 , Bosch Powertube 750Wh, Bosch Kiox 300

Fotogaléria



