

RAZE CARBON R, RACING SILVER/ORANGE, 2023

obj. č: 944872452



Technické špecifikácie

vyrábané veľkosti S: 380mm / M: 420mm / L: 450mm / XL: 500mm	rám Raze 29 Stealth Air full Carbon, Zero Suspension System, 130mm travel, Forward Geometry, Carbon Monoblock upper link, Boost 12x148mm rear axle, tapered head tube, 73mm BSA bottom bracket, dedicated 1x drivetrain design, HHG internal cable routing, Enduro MAX sealed bearings, shock mudguard, ISCG 05, custom frame protectors.
vidlica Fox 36 29 Float GRIP EVOL Performance, 150mm, tapered steerer tube, Boost 15x110mm axle, 44mm offset. Settings: 3 positions with micro adjust compression, low-speed rebound, air preload	hlavové zloženie Acros custom for 1-1/2
prehadzovačka Sram GX Eagle, Type 3 roller bearing clutch, cage lock, 1x12s, X-Actuation 1:1	radenie Sram Trigger NX Eagle, 12s, X-Actuation 1:1
brzdové páčky Sram G2, SwingLink, tool-free reach adjust	kluky Truvativ Stylo 7k Eagle, Boost, DUB axle, Direct mount chain ring, S/M size: 170mm, L/XL size: 175mm
stredové zloženie Sram DUB BSA, sealed bearings, 73mm	riadidlá Onoff Sulfur 1.0 double butted 6061 alloy, rise: 20mm, width: 800mm, 9° backsweep, 5° upsweep, 31.8mm barbare
predstavec Onoff Sulfur FG 30mm 0°, 6061 forged alloy, 31.8mm barbare	sedlovka Onoff Pija dropper internal, diameter 31.6mm, S size: 405x95-125mm, M size 458x120-150mm, L size: 498x140-170mm, XL size: 498x140-170mm
sedlo Fizik Antares R7	náboj predný Infinity hub, Boost 15x110mm, IS 6 bolts
náboj zadný Infinity hub, Boost 15x110mm, IS 6 bolts	reťaz Sram NX Eagle, 12s, Powerlock
kazeta Sram XG-1275, 10-52T, 12s	drôty 24 straight-pull double butted spokes
ráfiky Sram G2, SwingLink, tool-free reach adjust	plášte Maxxis Dissector 29x2.4 WT, tubeless ready, 3C MAXX TERRA compound, EXO+ protection, 120TPI, folding bead / Maxxis Aggressor 29x2.3, tubeless ready, dual compound, Exo protection, 60TPI, folding bead
obj.c. 010.23085	gripy Onoff Desert, 1lock-on, 135mm

tlmič

Fox Float DPS LV EVOL Performance, 205x57.5mm.
Settings: rebound, 3-position compression adjustment (Open/Mid/Lock), air preload. Trunnion top mount, 30x8mm bottom bushings

predná brzda

Sram G2 R, 4-piston caliper, Centerline 180mm IS 6 bolts one-piece rotor, steel-backed organic pads

zadná brzda

Sram G2 R, 4-piston caliper, Centerline 180mm IS 6 bolts one-piece rotor, steel-backed organic pads

nastavenia tlmiče

Light compression, light rebound, air volume spacer 0.6

prevodník

32T, CNC-machined alloy, X-SYNC 2

pätka k preházovalce

Sram UDH

Fotogaléria