

RAZE CARBON RR SL MIND, RACING SILVER/BRITISH RACING GREEN, 2023

obj. č.: 944872452

Odporúčaná cena

10.399 EUR

Akčná cena

8.129 EUR



Technické špecifikácie

vyrábané veľkosti S: 380mm / M: 420mm / L: 450mm / XL: 500mm	rám Raze 29 Stealth Air full Carbon, Zero Suspension System, 130mm travel, Forward Geometry, Carbon Monoblock upper link, Boost 12x148mm rear axle, tapered head tube, 73mm BSA bottom bracket, dedicated 1x drivetrain design, HHG internal cable routing, Enduro MAX sealed bearings, shock mudguard, ISCG 05, custom frame protectors. MIND System (EU only)
vidlica Fox 36 29 Float GRIP2 Factory Kashima, 150mm, tapered steerer tube, Boost 15x110mm axle, 44mm offset. Settings: high and low-speed compression, high and low-speed rebound, air preload	hlavové zloženie "Acros custom for 1-1/2"" head tube, angular contact bearings 40x52x7, Internal cable routing"
prehadzovačka Sram XX1 Eagle AXS, Type 2.1 roller bearing clutch, cage lock, long carbon cage, 1x12s, X-actuation 1:1	radenie Sram Eagle AXS Rocker paddle, 12s
brzdové páčky Sram G2 RSC, SwingLink, tool-free reach adjust	kluky Sram XX1 Eagle, Boost, DUB axle, Direct mount chain ring, S/M size: 170mm, L/XL size: 175mm
stredové zloženie Sram DUB BSA, sealed bearings, 73mm	riadidlá Onoff Krypton Carbon 1.0, rise: 25mm, width: 800mm, 9° backsweep, 5° upsweep, 31.8mm barbare
predstavec Onoff Krypton FG 30mm, CNC, 31.8mm barbare	sedlovka Fox Transfer Factory Kashima internal, diameter 31.6mm, S size: 363.5x125mm, M size: 418.3x150mm, L/XL size: 475.1x175mm
sedlo Fizik Antares R7	náboj predný Infinity hub, Boost 15x110mm, IS 6 bolts
náboj zadný Infinity hub, ID360 freewheel technology, Boost 12x148mm, IS 6 bolts	reťaz Sram GX Eagle, 12s, Powerlock
kazeta Sram XG-1295, 10-52T, 12s	drôty 24 straight-pull double butted spokes
ráfiky Mavic CrossMax Carbon XL R, 29 Boost 30mm internal width, hookless, tubeless ready, 24 spokes	plášte Maxxis Dissector 29x2.4 WT, tubeless ready, 3C MAXX TERRA compound, EXO+ protection, 120TPI, folding bead / Maxxis Aggressor 29x2.3, tubeless ready, dual compound, Exo protection, 60TPI, folding bead

obj.c.
010.23093

gripy
Onoff Desert, 1lock-on, 135mm

tlmič
Fox Float DPS Factory Kashima EVOL LV, 205x57.5mm.
Settings: Compression 3 positions lever, low-speed
compression, low-speed rebound, air preload. Trunnion
top mount, 30x8mm bottom bushings

predná brzda
Sram G2 RSC, 4-piston caliper, Centerline 180mm IS 6 bolts one-piece
rotor, steel-backed organic pads

zadná brzda
Sram G2 RSC, 4-piston caliper, Centerline 180mm IS 6
bolts one-piece rotor, steel-backed organic pads

nastavenia tlmiče
Light compression,light rebound, air volume spacer 0.6

prevodník
32T, CNC-machined alloy, X-SYNC 2

pätka k přehazovačce
Sram UDH

Fotogaléria

