

RAZE CARBON RR MIND, RACING SILVER/ÖHLINS YELLOW, 2022

obj. č.: 932626637



Technické špecifikácie

vyrábané veľkosti S: 380mm / M: 420mm / L: 450mm / XL: 500mm	rám New Trail 29 Stealth Air full Carbon, Zero Suspension System, 130mm travel, Forward Geometry, Carbon Monoblock upper link, Boost 12x148mm rear axle, tapered head tube, 73mm BSA bottom bracket, dedicated 1x drivetrain design, HHG internal cable routing, Enduro MAX sealed bearings, shock mudguard, ISCG 05, custom frame protectors.
vidlica Fox 36 29 Float GRIP2 Factory Kashima, 150mm, tapered steerer tube, Boost 15x110mm axle, 44mm offset. Settings: 3 positions with micro adjust compression, low-speed rebound, air preload	hlavové zloženie "Acros custom for 1-1/2"" head tube, angular contact bearings 40x52x7, Internal cable routing"
prehadzovačka Sram X01 Eagle, Type 3 roller bearing clutch, cage lock, 1x12s, X-Actuation 1:1	radenie Sram Trigger GX Eagle, 12s, X-Actuation 1:1
brzdové páčky Sram G2 RS, SwingLink, tool-free reach adjust	kluky Sram X1 Carbon Eagle, Boost, DUB axle, Direct mount chain ring, S/M size: 170mm, L/XL size: 175mm
stredové zloženie Sram DUB BSA, sealed bearings, 73mm	riadidlá Onoff Krypton Carbon 1.0, rise: 25mm, width: 800mm, 9° backsweep, 5° upsweep, 31.8mm barbare
predstavec Onoff Krypton FG 30mm, CNC, 31.8mm barbare	sedlovka Fox Transfer Factory Kashima internal, diameter 31.6mm, S size: 363.5x125mm, M size: 418.3x150mm, L/XL size: 475.1x175mm
sedlo Fizik Antares R7	náboj predný DT 350, Boost 15x110mm, IS 6 bolts
náboj zadný Maxxis Dissector 29x2.4 WT, tubeless ready, 3C MAXX TERRA compound, EXO+ protection, 120TPI, folding bead	reťaz Sram GX Eagle, 12s, Powerlock
kazeta Sram XG-1275, 10-52T, 12s	drôty DT Competition, straightpull
ráfiky DT Swiss XM1700 Spline 29, 30mm internal width, welded aluminum, tubeless ready, 28 spokes	plášte Maxxis Dissector 29x2.4 WT, tubeless ready, 3C MAXX TERRA compound, EXO+ protection, 120TPI, folding bead, Maxxis Aggressor 29x2.3, tubeless ready, dual compound, Exo protection, 60TPI, folding bead

obj.c.
010.22308

gripy
Onoff Diamond, 1lock-on, 135mm

tlmič

Fox Float DPS Factory Kashima evol LV, 205x57.5mm.
Settings: Compression 3 positions lever, low-speed compression, low-speed rebound, air preload. Trunnion top mount, 30x8mm bottom bushings

predná brzda

Sram G2 RS, 4-piston caliper, Centerline 180mm IS 6 bolts one-piece rotor, steel-backed organic pads

zadná brzda

Sram G2 RS, 4-piston caliper, Centerline 180mm IS 6 bolts one-piece rotor, steel-backed organic pads

nastavenia tlmiče

Light compression, extralight rebound, air volume spacer 0.6

prevodník

32T, CNC-machined alloy, X-SYNC 2

pätka k přehazovačce

Sram UDH

Fotogaléria

