

SUPERFOXY R, FROST GREEN/BLACK/ÖHLINS YELLOW, 2022

obj. č: 932626637



Odporúčaná cena

5.099 EUR

Technické špecifikácie

vyrábané veľkosti S: 380mm / M: 420mm / L: 470mm / XL: 510mm	rám SuperFoxy 29 6061 Alloy Stealth Evo, hydroformed tubing, Zero Suspension System, 160mm travel, Forward Geometry, one piece Monoblock upper link, SuperBoost 12x157mm rear axle, tapered head tube, 73mm BSA bottom bracket, dedicated 1x drivetrain design, telescopic seatpost internal routing, Max. capacity sealed bearings, ISCG 05
vidlica Öhlins RXF 38 M.2 29, 170mm, TTX18 Twin Tube cartridge, tapered steerer tube, Boost 15x110mm axle, offset 44mm. Settings: high speed compression lever with climb mode, low-speed compression, rebound, air preload, ramp chamber	hlavové zloženie Onoff Saturn tapered for 1-1/8" to 1-1/2" head tube, ACB sealed bearings, top 41x30.2x7x45°x45°, bottom 51.9x40x8x45°x45°
prehadzovačka Sram NX Eagle, Type 3 roller bearing clutch, cage lock, long cage, 1x12s, X-actuation 1:1	radenie Sram Trigger SX Eagle, 12s, X-Actuation 1:1
brzdové páčky Sram Code R, tool-free reach adjust	kluky Truvativ Descendant 7K Eagle, SuperBoost, DUB axle, Direct mount chain ring, S/M size: 170mm, L/XL size: 175mm
stredové zloženie Sram DUB BSA, sealed bearings, 73mm	riadidlá Onoff Sulfur 1.0 double butted 6061 alloy, rise: 20mm, width: 800mm, 9° backsweep, 5° upsweep, 31.8mm barbare
predstavec Onoff Sulfur FG 30mm 0°, 6061 forged alloy, 31.8mm barbare	sedlovka Onoff Pija dropper internal, diameter 31.6mm, S size: 337x100mm, M size 387x125mm, L size: 425x150mm, XL size: 465x170mm
sedlo SDG BEL-AIR 3.0, LPU foam, steel rails	náboj predný Mavic, Boost 15x110mm, IS 6 bolts
náboj zadný Mavic, SuperBoost 12x157mm, ID360 Ratched system, IS 6 bolts	reťaz Sram SX Eagle, 12s, Powerlock
kazeta Sram XG-1230, 11-50T, 12s	drôty Mavic J-bend duble butted
ráfiky Mavic Custom Deemax 29, 28mm internal width, Maxtal welded rim, tubeless ready, 28 spokes	plášte Maxxis Assegai 29x2.5WT, Maxxis Dissector 29x2.4WT, tubeless ready, 3C MAXX GRIP compound, DH casing, 60x2TPI, folding beadtubeless ready, 3C MAXX GRIP compound, DH casing, 60x2TPI, folding bead,
obj.c. 010.22076	gripy Onoff Diamond, 1lock-on, 135mm

tlmič

Öhlins TTX Air 205X65mm. Settings: high speed compression lever with climb mode, low-speed compression, rebound, air preload. Trunnion top mount, 22.2x10mm bottom bushings

predná brzda

Sram Code R, oversized 4-piston caliper, Centerline 200mm IS 6 bolts one-piece rotor, steel-backed metal sintered pads

zadná brzda

Sram Code R, oversized 4-piston caliper, Centerline 200mm IS 6 bolts one-piece rotor, steel-backed metal sintered pads

nastavenia tlmiče

C20 compression, R35 rebound

prevodník

32T, CNC-machined alloy, X-SYNC 2

pätka k prehadzovačce

Mondraker M068

Fotogaléria