

SUMMUM 29, DIRTY WHITE/ORANGE, 2023

obj. č: 944872452



Technické špecifikácie

vyrábané veľkosti S / M / L / XL	rám Summum 29 6061 Alloy Stealth Evo, hydroformed tubing, Zero suspension system, 200mm travel, Forward Geometry, alloy upper link with shock eyelet bearings, SuperBoost 12x157mm rear axle, 83mm BSA bottom bracket, MAX. capacity dual row Enduro bearings, HHG internal cable routing, ISCG 05. *Optional Geometry kit
vidlica Rockshox Boxxer Select RC 29, 200mm, DebonAir, 1-1/8" steerer tube, Boost 20x110mm axle, offset 56mm. Settings: low-speed compression, rebound, air preload	hlavové zloženie Onoff Mercurium 1.5 ZS for 1-1/8" steerer tube, 41x30.15x7x45°x45° ACB sealed bearings, geometry kit cups, external diameter 56mm
prehadzovačka Sram GX DH, 7s, medium cage, X-actuation 1:1	prešmykač E.13 Vario Compact Upper Slider ,Alloy backplate ,DMB (Direct mount Bashguard) Lower Slider 34-36t, ISCG 05 adjustable upper slider
radenie Sram trigger GX DH 7s, X-actuation 1:1	brzdové páčky Sram DB8, tool-free reach adjust
kluky Truvativ Descendant DH, DUB axle, Direct mount chain ring, 165mm	stredové zloženie Sram DUB BSA, sealed bearings, 83mm
riadidlá Onoff Sulfur 1.0 double butted 6061 alloy, rise: 20mm, width: 800mm, 9° backsweep, 5° upsweep, 31.8mm barbore	predstavec Onoff Krypton DH CNC Integrated FG, 25-30mm adjustable length, 31.8mm barbore, 6061 alloy, 2x6mm spacer
sedlovka SDG Micro I-Beam SP-751 Alloy, diameter 31.6mm, length 300mm, micro-adjustment	sedlo SDG I-Fly 2.0 I-Beam, high-density PU foam, Cordura sides
náboj predný MDK DA4371B-M20, Boost 20x110mm, IS 6 bolts	náboj zadný MDK DA4352B, 12x157mm, sealed bearings, IS 6 bolts
reťaz Sram PC1110 11s, Powerlock	kazeta Sram PG 720 11-25T, 7s
drôty CN stainless steel	ráfiky MDK-DP1 29, 27mm internal width, 32 holes
plášte Michelin DH34 29x2.4, tubeless ready, Magi-X DH compound, double-reinforced DH shield casing, wire bead	obj.c. 010.23153
gripy Onoff Twin, 1lock-on, 135mm	tlmič Rock Shox Super Deluxe Coil Select R, 225x70mm. LNM ST B1, Linear rebound, Medium compression, spring preload. Trunnion top mount, 30x8mm bottom bushings

predná brzda

Sram DB8, oversized 4-piston caliper, Centerline 220mm IS 6 bolts one-piece rotor, steel-backed metal sintered pads

zadná brzda

Sram DB8, oversized 4-piston caliper, Centerline 203mm IS 6 bolts one-piece rotor, steel-backed metal sintered pads

nastavenia tlmiče

Medium compression, linear rebound. Spring rate: S size 400 lbs, M size 400 lbs, L size 450 lbs, XL size 500 lbs

prevodník

34T, steel, X-SYNC

pätka k preházovalce

Mondraker M068

Fotogaléria