

FOXY CARBON R 29 MIND, CHERRY RED/CARBON, 2022

obj. č: 932626637



Odporúčaná cena

5.999 EUR

Technické špecifikácie

vyrábané veľkosti S: 380mm / M: 420mm / L: 450mm / XL: 500mm	hmotnosť 14,1 Kg
rám Foxy 29 Stealth Air full Carbon, Zero Suspension System, 150mm travel, Forward Geometry, aluminium CSC upper link with carbon bridge, Boost 12x148mm rear axle, tapered head tube, 73mm BSA bottom bracket, dedicated 1x drivetrain design, HHG internal cable routing, Enduro MAX sealed bearings, shock mudguard, ISCG 05, custom frame protectors. *Optional Geometry Kit	vidlica Fox 36 29 Float FIT GRIP EVOL Rhythm, 160mm, tapered steerer tube, Boost 15x110mm axle, offset 44mm. Settings: sweep adjust compression, low-speed rebound, air preload
hlavové zloženie Acros custom for 1-1/2	prehadzovačka Sram Trigger NX Eagle, 12s, X-Actuation 1:1
radenie Sram Trigger NX Eagle, 12s, X-Actuation 1:1	brzdové páčky Sram G2 R, tool-free reach adjust
kluky Truvativ Descendant 6K Eagle, Boost, DUB axle, Direct mount chain ring, S/M size: 170mm, L/XL size: 175mm	stredové zloženie Sram DUB BSA, sealed bearings, 73mm
riadidlá Onoff Sulfur 1.0 double butted 6061 alloy, rise: 20mm, width: 800mm, 9° backsweep, 5° upsweep, 31.8mm barbare	predstavec Onoff Sulfur FG 30mm 0°, 6061 forged alloy, 31.8mm barbare
sedlovka Onoff Pija dropper internal, diameter 31.6mm, S size: 387x125mm, M size: 425x150mm, L/XL size: 465x170mm	sedlo SDG BEL-AIR 3.0, LPU foam, steel rails
náboj predný DT 370, Boost 15x110mm, IS 6 bolts	náboj zadný DT 370, Boost 12x148mm, 18T Ratched LN system, IS 6 bolts
reťaz Sram NX Eagle, 12s, Powerlock	kazeta Sram XG-1230, 11-50T, 12s
drôty DT Champion, straightpull	ráfiky DT Swiss E1900 Spline 29, 30mm internal width, sleeved aluminum, tubeless ready, 28 spokes
plášte Maxxis Minion DHF 29x2.5 WT, tubeless ready, 3C MAXX TERRA compound, EXO+ protection, 120TPI, folding bead, Maxxis Minion DHR II 29x2.4 WT, tubeless ready, 3C MAXX TERRA compound, EXO+ protection, 120TPI, folding bead	obj.c. 010.22316
gripy Onoff Diamond, 1lock-on, 135mm	tlmič Fox Float-X LV Performance, 205x65mm. Settings: compression 2 positions lever, low-speed rebound, air preload. Trunnion top mount, 30x8mm bottom bushings

predná brzda

Sram G2 R, 4-piston caliper, Centerline 200mm IS 6 bolts one-piece rotor, steel-backed organic pads

zadná brzda

Sram G2 R, 4-piston caliper, Centerline 180mm IS 6 bolts one-piece rotor, steel-backed organic pads

nastavenia tlmiče

Light compression, light rebound, air volume spacer 0.6

prevodník

32T, steel, X-Sync 2

pätka k preházovalce

Sram UDH

ostatné

*Optional Geometry kit: steering cups: +/- 1°

Fotogaléria