

CHRONO 29, DIRTY WHITE/BLACK, 2022

obj. č.: 932626637



Odporúčaná cena

1.349 EUR

Technické špecifikácie

vyrábané veľkosti S: 395mm / M: 430mm / L: 470mm / XL: 520mm	rám Chrono 29 6061 Xtralite Alloy butted, XC Forward Geometry, 73mm BSA bottom bracket, tapered head tube, HHG Internal Cable Routing, Boost 12x148mm rear axle
vidlica RockShox Judy Silver TK 29, 100mm, TurnKey, Solo Air, tapered steerer tube, 9x100mm axle, 30mm steel stanchions, 46mm offset. Settings: Poplock 2 pos remote compression (open/lock), rebound, air preload	hlavové zloženie Onoff Saturn tapered for 1-1/8" to 1-1/2" head tube, ACB sealed bearings, top 41x30.2x7x45°x45°, bottom 51.9x40x8x45°x45°
prehadzovačka Sram SX Eagle, Type 3 roller bearing clutch, cage lock, long cage, 1x12s, X-actuation 1:1	radenie Sram Trigger SX Eagle, 12s, X-Actuation 1:1
brzdové páčky Sram Level, tooled reach adjust, lever pivot bushings	kluky Sram SX Eagle, Boost, DUB axle, Direct Mount chain ring, S size: 170mm, M/L/XL size: 175mm
stredové zloženie Sram DUB BSA, sealed bearings, 73mm	riadidlá Onoff Sulfur 0.2, double butted 6061 alloy, rise: 4.8mm, width: 740mm, 9° backsweep, 0° upsweep, 31.8mm barbare
predstavec Onoff Sulfur, 6061 T6 Alloy, 31.8mm barbare, rise: +/-7°, length: sizes S/M: 60mm, size L: 80mm, size XL: 90mm	sedlovka Onoff Sulfur 0-R, 6061 T6 Alloy, 3D forged, diameter 27.2mm, length 400mm
sedlo Mondraker XC Series, steel rail	náboj predný Formula DC20LW, 9x100mm, cup cone ball bearings, IS 6 bolts
náboj zadný Formula MST148S-4SB, Boost 12x148mm, sealed bearings, IS 6 bolts, MS freehub	reťaz Sram SX Eagle, 12s, Powerlock
kazeta Sram PG-1210, 11-50T, 12s	drôty CN round stainless steel
ráfiky MDK-XP1 29 TLR, 25mm internal width, tubeless ready, 32 spokes	plášte Maxxis Ikon 29x2.20, 60TPI, wire bead, Maxxis Ikon 29x2.20, 60TPI, wire bead
obj.c. 010.22008	gripy Onoff Diamond, 1lock-on, 135mm
predná brzda Sram Level, 2 piece caliper, Centerline 160mm IS 6 bolts one-piece rotor, steel-backed organic pad	zadná brzda Sram Level, 2 piece caliper, Centerline 160mm IS 6 bolts one-piece rotor, steel-backed organic pad
prevodník 34T, steel, X-Sync 2	pätka k prehadzovačke Mondraker M068

Fotogaléria

