

FOXY 29, RACING SILVER/BLACK, 2022

obj. č: 932626637



Odporúčaná cena

3.699 EUR

Akčná cena

2.799 EUR

Technické špecifikácie

vyrábané veľkosti S: 380mm / M: 420mm / L: 470mm / XL: 510mm	hmotnosť 15,5 Kg
rám Foxy 29 6061 Alloy Stealth Evo, hydroformed tubing, Zero Suspension System, 150mm travel, Forward Geometry, one piece Monoblock upper link, Boost 12x148mm rear axle, 73mm BSA bottom bracket, dedicated 1x drivetrain design, telescopic seatpost internal routing, MAX capacity sealed bearings, ISCG 05	vidlica Fox 36 29 Float FIT GRIP EVOL Rhythm, 160mm, tapered steerer tube, Boost 15x110mm axle, offset 44mm. Settings: sweep adjust compression, low-speed rebound, air preload
hlavové zloženie Onoff Saturn tapered for 1-1/8" to 1-1/2" head tube, ACB sealed bearings, top 41x30.2x7x45°x45°, bottom 51.9x40x8x45°x45°	prehadzovačka Sram SX Eagle, Type 3 roller bearing clutch, cage lock, long cage, 1x12s, X-actuation 1:1
radenie Sram Trigger SX Eagle, 12s, X-Actuation 1:1	brzdové páčky Sram G2 R, tool-free reach adjust
kľuky Sram SX Eagle, Boost, DUB axle, Direct Mount chain ring, S/M size: 170mm, L/XL size: 175mm	stredové zloženie Sram DUB BSA, sealed bearings, 73mm
riadidlá Onoff Sulfur 1.0 double butted 6061 alloy, rise: 20mm, width: 800mm, 9° backsweep, 5° upsweep, 31.8mm barbare	predstavec Onoff Sulfur FG 30mm 0°, 6061 forged alloy, 31.8mm barbare
sedlovka Onoff Pija dropper internal, diameter 31.6mm, S size: 337x100mm, M size 387x125mm, L size: 425x150mm, XL size: 465x170mm	sedlo SDG BEL-AIR 3.0, LPU foam, steel rails
náboj predný DT 370, Boost 15x110mm, IS 6 bolts	náboj zadný DT 370, Boost 12x148mm, 18T Ratched LN system, IS 6 bolts,
reťaz Sram SX Eagle, 12s, Powerlock	kazeta Sram PG-1210, 11-50T, 12s
drôty DT Champion, straightpull	ráfiky DT Swiss E1900 Spline 29, 30mm internal width, sleeved aluminum, tubeless ready, 28 spokes
plášte Maxxis Minion DHF 29x2.5 WT, tubeless ready, 3C MAXX TERRA compound, EXO+ protection, 120TPI, folding bead, Maxxis Aggressor 29x2.3, tubeless ready, dual compound, Exo protection, 60TPI, folding bead	obj.c. 010.22064

gripy

Onoff Diamond, 1lock-on, 135mm

tlmič

Fox Float DPS LV EVOL Performance, 205x62.5mm.
Settings: rebound, 3-position compression adjustment (Open/Mid/Lock), air preload. Trunnion top mount, 22.2x10mm bottom bushings

predná brzda

Sram G2 R, 4-piston caliper, Centerline 200mm IS 6 bolts one-piece rotor, steel-backed organic pads

zadná brzda

Sram G2 R, 4-piston caliper, Centerline 180mm IS 6 bolts one-piece rotor, steel-backed organic pads

nastavenia tlmiče

Light compression, extralight rebound, air volume spacer 0.6

prevodník

32T, steel, X-Sync 2

pätka k preházovalce

Mondraker M068

Fotogaléria